

**CLAIMS LISTING:**

1. (Currently amended) A protection device (10) for protecting a brake disk (12) in a disk brake from dirt particles, said protection device comprising:

at least one protection means (13) configured to cover at least partly a radially outward face of the brake disk for effectively preventing dirt particles and ~~relative-on-coming, travel generated~~ wind from directly striking a brake disk (12) associated therewith when said protection means (13) is disposed in a first end position and configured to expose at least partly the radially outward face of the brake disk for allowing relative wind to directly strike said brake disk (12) associated therewith when disposed in a second end position, ~~wherein said at least one protection means (13) for partly surrounding said brake disk (12) when installed therewith and;~~ ~~mountable on a vehicle's wheel suspension (11);~~ said at least one protection means (13) ~~being~~ is at least partly constructed from material that is shape-influenced by heat such that said at least one protection means (13) assumes said first end position when a temperature of said protection means (13) lies below a first temperature and assumes said second end position when said protection means (13) exceeds a second temperature.

2. (Previously Presented) The protection device as recited in claim 1, wherein the shape of said protection means (13) changes continuously from said first end position to said second end position.

3. (Previously Presented) The protection device as recited in claim 1, wherein the shape of said protection means (13) changes stepwise from said first end position to said second end position.

4. (Previously Presented) The protection device as recited in claim 1, wherein said protection device is fixedly disposed relative to a brake caliper of said disk brake.

5. (Previously Presented) The protection device as recited in claim 1, wherein the shape of said protection means (13) is reactive to heat radiation from said brake disk (12).

6. (Previously Presented) The protection device as recited in claim 1, wherein said protection

means (13) further comprises a plurality of radial tongues having radially inner ends connectable to said wheel suspension (11) of a vehicle.

7. (Cancelled)

8. (Withdrawn) The protection device as recited in claim 1, wherein said protection means (13) further comprises a plurality of peripherally movable tongues disposed along an outer edge of said protection device.

9. (Withdrawn) The protection device as recited in claim 1, wherein said protection means (13) includes an opening (14) that assumes the form of a sector-shaped arc portion when said protection means (13) is disposed in said second end position.

10. (Previously presented) The protection device as recited in claim 1, wherein said protection means (13) is L-shaped.

11. (Previously presented) The protection device as recited in claim 10, wherein said material that is shape-influenced by heat is disposed in an angle between two legs (13a, 13b) of said L-shaped protection means (13).

12. (Previously Presented) The protection device as recited in claim 1, wherein said material that is shape-influenced by heat is disposed at a radially inner end of said protection means (13).

13. (Previously Presented) The protection device as recited in claim 1, wherein said protection means (13) is comprised, at least partially, of a bimetal.

14. (Previously Presented) The protection device as recited in claim 1, wherein said protection device is configured to be disposed sufficiently close to said brake disk (12) such that said protection device absorbs and dissipates heat from said brake disk (12).

15. (Currently amended) A protected vehicular disk brake arrangement shielded from

contamination particles, said arrangement comprising:

a contamination shield (13) mounted to a suspension of a carrying vehicle and surrounding an associated brake disk (12), said shield being at least partly constructed from temperature reactive material characterized by being shape-influenced by heat produced by the associated brake disk (12) when performing a braking function and thereby varying an amount of cooling air supplied to the associated brake disk (12) in dependence upon brake temperature; and

said contamination shield (13) having a closed configuration that at least partially covers a radially outward face of the brake disk thereby precluding ~~precludes~~ contamination particulate and on-coming, travel generated cooling air from directly striking the associated brake disk (12) and an open configuration that exposes at least partly the radially outward face of the brake disk thereby allowing on-coming, travel generated ~~allows~~ cooling air to directly strike the associated brake disk (12), the closed configuration being assumed when a temperature of the contamination shield (13) lies below a first predetermined temperature and the open configuration being assumed when the temperature of the contamination shield (13) exceeds a second predetermined temperature.

16. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) is adapted to change shape continuously between the open and closed configurations.

17. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) is adapted to change shape stepwisely between the open and closed configurations.

18. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) is fixedly located proximate a brake caliper.

19. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) further comprises a plurality of radially extending tongues.

20. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) further comprises a plurality of peripherally movable tongues.

21. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) is L-shaped.

22. (Original ) The arrangement as recited in claim 21, wherein the temperature reactive material is located in an angle between two legs (13a, 13b) of the L-shaped contamination shield (13).

23. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) is comprised, at least partially, by a bimetal.

24. (Original) The arrangement as recited in claim 15, wherein the contamination shield (13) is located sufficiently close to the associated brake disk (12) to absorb and dissipate heat therefrom.

25. (New) A protection device for protecting a brake disk in a disk brake from dirt particles, said protection device comprising:

at least one protection cover mountable on a vehicle's wheel suspension, said at least one protection cover being at least partly constructed from material that is shape-influenced by heat such that said at least one protection cover assumes a first position that at least partly covers a forward radial face of the brake disk thereby effectively preventing dirt particles and on-coming, travel generated wind from directly striking the forward radial face of the brake disk when a temperature of said protection cover lies below a first temperature, and assumes a second end position that exposes the forward radial face of the brake disk thereby allowing on-coming, travel generated wind to directly strike said forward radial face of the brake disk associated therewith when said protection cover exceeds a second temperature.